

REINO

Wall Mounted Series





MyECO
R32

inverter WiFi








Horse Power (HP)	1.0	1.5	2.0	2.5	3.0
REINO Series	Indoor Unit				
	A3WMY10BNF2	A3WMY15BNF2	A3WMY20BNF2	A3WMY25BNF2	A3WMY30BNF2
					
					
	Outdoor Unit				
	A3LCY10BN2	A3LCY15BN2	A3LCY20BN2	A3LCY25BN2	A3LCY30BN2
					

R32 Refrigerant

Greenery Refrigerant


Acson MyEco offers eco-friendly products which lead to a more environmentally friendly and sustainable future. R32 refrigerant contributes to zero Ozone Depletion potential and the reduction of global warming potential up to 30% when compared with R410A and R22 refrigerant. It is everyone's responsibility to take care of our mother earth to make this planet a better place for our communities and generations to come.



The R32 refrigerant has lower Global Warming Potential (GWP), which is one third lower than R410A.

Inverter

Inverter is able to electronically control the electrical voltage, current and frequency by receiving information from sensors. It can regulate the compressor revolution speed and adjust the air conditioning output, resulting in minimization of temperature fluctuation.






Filtronz+ Filter

Filtronz+ Filter effectively decompose virus and reduce bacteria & fungus on the air filter surface.




Decomposition of Viruses

The effectiveness rate of virus decomposition is increased by 99% in 2 hours



Reduction of Bacteria

The effectiveness rate of bacteria reduction is more than 99.99% in 24 hours



Reduction of Fungus


Generation of fungus achieved Grade 0 in 24 hours (No fungus visible under the microscope)



**Image is for illustration purposes*


How Filtronz+ Filter works?

Step 1




Silver ions (Ag+) on the filter absorb virus to the filter surface

Step 2



Combination of organic and inorganic components simultaneously react to change the protein that exists on the virus surface

Step 3



Enzyme protein inactivated, thus the viruses are decomposed and prevented from spread

Indoor Coil Maintenance with iClean+ & iClean



i-Clean+ is an exclusive Acson technology where the indoor cooling coil of the air conditioner is cleaned using dew condensation to partially remove attached dust or mold.



iClean is a new feature which will automatically dried the indoor cooling coil to prevent mold & bacteria growth.


***Only Applicable to 2 & 2.5HP only**



***Activated via MY Acson Mobile Apps only.**

ULTRA Printed Circuit Board (PCB)

Acson's ULTRA Printed Circuit Board (PCB) are specially strengthened to withstand voltage fluctuations. This allow our PCB to operate across wide ranges of voltages in areas with unstable power supply. With new ULTRA PCB, the air conditioner unit are able to operate at 150V to 264V, and able to withstand voltage fluctuations from 0V to 440V.



Anti Corrosion Blue Fin

The outdoor unit is protected with anti corrosion blue fin, which is a type of protective layer coating on the fin which can prolong the lifespan of the unit.

With anti corrosion blue fin, the condensor coil is more resistant to corrosion, rust and rain without affect the cooling performance.

**Not applicable to model A3WMY30BNF2.*




Turbo Mode

Turbo Mode provided maximum cooling effect to user who seek for instant cooling.

Once activated, fan speed will run at turbo mode and compressor will run in maximum frequency to provide maximum cooling capacity.



This enables the set temperature to be achieved faster.



Sleep Mode

Sleep mode ensures a comfortable environment for restful sleep. As ambient temperature at night decreased, set temperature is increase gradually according to normal sleeping temperature.

Also it automatically dim down the LED display intensity when sleep mode is activated which allow user to rest with minimum disturbance from LED light.



**Maximum capacity decreases during Save Mode, requiring more time to reach the set temperature.*

Save Mode

Save mode is an intelligent feature that ensure optimum energy consumption while fulfilling basic human comfort needed.

The Save mode reduces the maximum operating current and power consumption by approximately 30% during activation by limiting compressor frequency



Specification

Dimension	Height (mm)	32
	Width (mm)	50
	Depth (mm)	15
Wi-Fi Frequency		2.4GHz
Network Configuration		
Out-of-home Control		Internet
In-home Control		LAN, Bluetooth
Electrical Specification		
Communication Protocol		NS
Input Supply	Voltage	5V
	Current	150 mA
	Power Consumption	750 mW
Supported OS		Android 5 or later; IOS 9 or later



Acson Wifi Adapter, AWM01A01



MY Acson App

A single swipe on the phone application which designed with simple control user interface. MY Acson is currently available for both Android & IOS system.




MY Acson



MY Complete Control

- Setting different modes (e.g. cool, dry, fan, turbo, sleep, quiet mode)
- Controlling fan speed, air flow direction & temperature settings
- Controlling the Zoning System



MY Convenience

- Set 7-day schedules & timers that adjust AC according to your lifestyle
- Control every AC unit from your couch - no need to go racing room-to-room changing settings
- Guest sharing option - possible to be both hospitable and safe



MY Comfort

- Pre-cool your room whilst still in the workplace or office.
- Room is already pre-cooled according to your desired settings as you reach home.



MY Energy-Efficient

- Monitor and track energy consumption for better budget planning

*subject to applicable model

GeoFencing

Smart Comfort, Automatically Yours

Experience the New Geofencing Feature

Your AC now works around your lifestyle. Using smart location technology, your home stays cool when you're there and saves energy when you're not.


Arriving Home (Auto-ON):

Set a distance (up to 8km) to pre-cool your home before you even reach the door.

Leaving Home (Auto-OFF):

Never worry about forgetting to turn off the AC again- it powers down automatically as you drive away.

Note: To enjoy this hands-free comfort, please set your phone's location permission to "Always On."



Specifications

REINO Wall Mounted Series

REINO

Model	Indoor Unit			A3WMY10BNF2	A3WMY15BNF2	A3WMY20BNF2	A3WMY25BNF2	A3WMY30BNF2
	Outdoor Unit			A3LCY10BN2	A3LCY15BN2	A3LCY20BN2	A3LCY25BN2	A3LCY30BN2
Nominal Cooling Capacity		BTU/h		9,500 (3,400-11,000)	12,300 (4,100-13,000)	19,000 (6,000-21,200)	24,000 (6,600-24,500)	25,600 (7,900-29,000)
		kW		2.78 (1.00-3.22)	3.60 (1.20-3.81)	5.57 (1.76-6.21)	7.03 (1.93-7.18)	7.50 (2.32-8.50)
Nominal Total Input Power		W		870	1,165	1,590	1,965	2,180
Nominal Running Current		A		3.93	5.24	6.99	8.61	9.71
EER		W/W		3.20	3.09	3.50	3.58	3.44
CSPF		Wh/Wh		5.40	5.40	5.10	5.50	5.60
Power Supply		V/Ph/Hz		Power From Indoor				
				220 - 240/1/50				
MEPS RATING								Not Applicable

Indoor Unit	Control	Wifi control		Built In				
		Operation		LCD Remote Control / WiFi Control				
		Air Discharge		Automatic Louver (Up & Down)				
	Air Flow	Turbo	I/s(CFM)	193 (410)	198 (420)	212 (450)	340 (720)	359 (760)
		High	I/s(CFM)	179 (380)	188 (400)	203 (430)	302 (640)	336 (700)
		Medium	I/s(CFM)	146 (310)	155 (330)	179 (380)	264 (560)	264 (560)
		Low	I/s(CFM)	108 (230)	118 (250)	137 (290)	227 (480)	227 (480)
		Quiet	I/s(CFM)	90 (190)	94 (200)	123 (260)	170 (360)	170 (360)
	Sound Pressure Level (H/M/L/Q)		dBA	39/33/26/21	39/34/26/21	42/39/32/29	43/41/36/30	44/41/36/30
	Unit Dimension	Height	mm(in)	280 (11.02)	288 (11.32)		297 (11.68)	297 (11.68)
		Width	mm(in)	730 (28.74)	770 (30.27)		990 (38.92)	990 (38.92)
		Depth	mm(in)	213 (8.39)	234 (9.20)		273 (10.73)	273 (10.73)
	Packaging Dimension	Height	mm(in)	293 (11.54)	327 (12.87)		371 (14.61)	371 (14.61)
		Width	mm(in)	796 (31.34)	830 (32.68)		1073 (42.24)	1073 (42.24)
		Depth	mm(in)	360 (14.17)	363 (14.29)		375 (14.76)	375 (14.76)
Unit Weight		kg(lb)	8.5 (18.74)	9.0 (19.84)		13.0 (28.66)	13.0 (28.66)	
Condensate Drain Size		mm(in)	19.05					

Outdoor Unit	Air Flow		I/s(CFM)	342.19 (725)	519.18 (1100)	769.30 (1630)	656.06 (1390)	1,032 (2186)	
	Sound Pressure Level (H/M/L/Q)		dBA	48	48	49	52	53	
	Unit Dimension	Height	mm(in)	418 (16.46)	550 (21.65)	615 (24.21)		695 (27.36)	
		Width	mm(in)	695 (27.36)	675 (26.57)	845 (33.27)		930 (36.61)	
		Depth	mm(in)	244 (9.60)	284 (11.18)	300 (11.81)		350 (13.78)	
	Packaging Dimension	Height	mm(in)	480 (18.90)	610 (24.01)	679 (26.73)		760 (29.92)	
		Width	mm(in)	807 (31.77)	801 (31.54)	992 (39.06)		1,084 (42.68)	
		Depth	mm(in)	340 (13.39)	384 (15.11)	414 (16.30)		473 (18.62)	
	Unit Weight		kg(lb)	18 (39.68)	21 (46.30)	33 (72.75)	37 (81.75)	40 (88.18)	
	Fin Spec			Anti Corrosion Blue Fin					PFC Coil
	Pipe Connection	Liquid	mm(in)	6.4(1/4)					9.5 (3/8)
		Gas	mm(in)	9.5 (3/8)			12.7 (1/2)		15.9 (5/8)
Maximum Piping Length		m	20	20	30	30	35		
Maximum Piping Height		m	15	15	20	20	20		

Refrigerant Type				R32				
------------------	--	--	--	-----	--	--	--	--

CSPF = Cooling Seasonal Performance Factor
MEPS = Minimum Energy Performance Standard

- All specifications are subject to change by the manufacturer without prior notice.
- Nominal Cooling Capacity is based in the conditions: Cooling 27°C DB / 19°C WB indoor and 35°C DB / 24°C WB outdoor.
- Sound Pressure Level is according to JIS C 9612 standard. Position of the measurement point is 1m in front and 0.8m below the unit.
- Units are tested & compiled to international standards such as ISO 5151.



*3 years of Parts & Labour coverage.

*Applicable during promotion period 1st April 2026 to 31st March 2028.



ACSON MALAYSIA SALES & SERVICE SDN.BHD.
*a member of **DAIKIN** group*

Business Registration NO.198401017130 (129688-D)


No. 7A, Jalan 13/4, Seksyen 13, 46200 Petaling Jaya,
Selangor Darul Ehsan, MALAYSIA.

Tel : +603 7964 8200 Sales Fax : +603 7956 9909

Service Fax : +603 7956 9907 Acson Careline : 1300 22 3344

Penang	: +604-5377 176	Pahang	: +609-5178 696
Perak	: +605-3129 828	Kelantan	: +609-7405 233
Melaka	: +606-2926 196	Sarawak	: +6082-344 128
Johor	: +607-3551 599	Sabah	: +6088-420 205

Authorized Dealer :



Products manufactured in an ISO certified facility.
This document contains the most current product information as of this printing.
For the most up-to-date product information, please logon to www.acson.com.my

CAT-A3WMYBNF2-2603

www.acson.com.my | AcsonMalaysia